


WIRING OPTION 2

1	Power (+)	(18-32VDC)
2	Return (-)	
3	Manual Bit	
4	Fault Relay] (N.C.)
5	Fault Relay	
6	Alarm Relay (N.O.)	
7	Alarm Relay (C)	
8	Alarm Relay (N.C.)	
9	4-20mA Out (Source)	
10	RS 485 (+)	
11	RS 485 (-)	
12	RS 485 (GND)	



ITEM LIST/NOTES

- PART NO.
STD DETECTOR : 40/40-211SC
HIGH TEMP. DETECTOR : 40/40-221SC
BRACKET : 40/40-001
- MATERIAL : 316 SS
- CABLE ENTRY : 2xM25

Aa		ECO02065	24.09.17	IZOTOV E.						
SYL	DESCRIPTION	DATE	APPROVAL	ITEM	QTY	PART NO.	CAT. NO.	DESCRIPTION		
REVISIONS						PARTS LIST				
TOLERANCES		SCALE 1:1		DIMENSIONS ARE IN MM		 IR3 FLAME DETECTOR ASSY WITH TILT				
MM /	DEGREES /	TRACED	V.N.	20.03.08						
MATERIAL		DRAWN	NELA	20.03.08	SURFACE TEXTURE AS PER ANSI-B46.1					
		CHECKED	SERERO S.	24.09.17	SUBMITTED					
		MAMAN A.			APPROVED					
NEXT ASSY		SERERO S. 24.09.17			SIZE C		DWG. NO. OL-777802-3		SHEET 1 OF 1	