



Model No.: 40/40I - XXXSX

- | | | |
|-----------------|----------|---|
| Wiring Option | Approval | C - ATEX, IECEx |
| Temp. Range | | F - FM, CSA |
| 1 - 167°F(75°C) | | B - INMETRO |
| 2 - 185°F(85°C) | | E - ATEX, IECEx with encapsulated E.O.L. resistor |
| Cable Entry | | |
| 1 - M25x1.5P | | |
| 2 - 3/4"-14NPT | | |

MATERIAL: St.St. 316L.

WEIGHT: 2.8Kg. [6.1Lb]

Ja	ECO02065	19.09.17	I ZOTOV E.

SYM.	DESCRIPTION	DATE	APPROVAL	ITEM	QUAN	PART NO.	CAT. NO.	DESCRIPTION
REVISIONS				PARTS LIST				

TOLERANCES		SCALE	1:2
MM /	DEGREES /	TRACED	SHAUL 22.01.15
MATERIAL	/	DRAWN	MILA 22.01.15
		CHECKED	SERERO S. 19.09.17
		SUBMITTED	
		APPROVED	
NEXT ASSY			

DIMENSIONS ARE IN MM	
SURFACE TEXTURE AS PER ANSI-B46.1	

SPECTREX			
IR3 FLAME DETECTOR ASSY			
SIZE	DWG. NO.	SHEET	OF
B	0L-777802	1	1