

Spectrex SharpEye™ 40/40C-LB

Integrated Ultraviolet/Infrared Flame Detector



The SharpEye 40/40C-LB Ultraviolet/Infrared (UV/IR) Flame Detector is part of the leading, next generation SharpEye 40/40 series.

Featuring fast detection in under five seconds with proven immunity to false alarms, the integrated UV and IR optical sensors detect flames with a large variety of hazardous sources, such as hydrocarbon-based fuel and gas, hydroxyl, hydrogen, metal, inorganic, etc., ensuring flawless performance to keep a SharpEye on your safety!



Features and benefits

- Advanced long distance detection of hydrogen and hydrocarbon-based fuel and gas fires at up to 50 ft (15 m)
- Extended detection range more than doubles detection coverage
- Proven false alarm immunity
- Unparalleled reliability - 150,000 hours MTBF
- Wide temperature range:
-40 °F (-40 °C) to +167 °F (+75 °C)
- Worldwide and regionally certified for hazardous areas
- Performance and reliability approved by recognizable certification bodies
- SIL3 compatible
- Enhanced durability backed up by with three-year warranty
- Innovative ultraviolet (UV) and infrared (IR) built-in test - continuously validating the optical integrity and the electronic circuitry
- Multiple output options for maximum compatibility with standard infrastructures
- Plug and play - factory calibrated for immediate use in any fire detection system
- Universal wiring option for fast ordering process
- Two sensitivity levels, adapting to any application
- Heated optic for impeccable performance in challenging environmental conditions
- Internal log event recorder to analyze past events

Contents

Features and benefits.....	2
Applications.....	3
Ordering information	4
Specifications.....	6
Approvals.....	8

Applications

- Oil and gas onshore and offshore installations and pipelines
- Explosives and munitions
- Petrochemical and chemical plants
- Storage tank farms
- Aircraft hangars
- Power generation facilities
- Pharmaceutical industry
- Printing industry
- Refinery hydrogenation
- Warehouses
- Automotive industry
- Waste disposal facilities
- Aerospace industry
- Hydrogen fuel cell industry
- Hydrogen vehicle parking and refueling
- Battery charging areas
- Space industry hydroxyl propellant
- Static fuel cell systems
- Light industrial

Ordering information

[VIEW PRODUCT >](#)

Model

Code	Description
-LB	Ultraviolet/infrared (UV/IR)

Wiring

Code	Description
-6	Universal

Operating temperature range

Code	Description
4	-40 °F (-40 °C) to +167 °F (+75 °C)

Electrical cable entries

Code	Description
1	M25
2	¾-in. NPT

Enclosure

Code	Description
A	Aluminum polyurethane painted

Hazardous area approvals

Code	Description
B	INMETRO
F	USA and Canada Explosion-Proof ⁽¹⁾
C	ATEX/IECX/UKCA
R	EAC CU TR

(1) Aluminum enclosure: FM, FMC

Tilt mount

Code	Description
Y	Including tilt mount stainless steel 316
N	Without tilt mount

Protective cover

Code	Description
7	ABS plastic
8	Stainless steel 316

Accessories

Part number	Description
FS-1200	Flame simulator (ex proof)
877090	Tilt mount
877670	Flame detector duct mount assembly
789260-2	Flame detector pole mount assembly, 2 in.
789260-1	Flame detector pole mount assembly, 3 in.
789260-3	Flame detector pole mount assembly, 4 in.
794079	USB RS-485 harness kit
877650	Flame detector air shield assembly
877263	Protective cover (Plastic)
877163	Protective cover (Stainless steel)
877563	Field of view limiter

Specifications

Table 1: Detection ranges

At highest sensitivity setting for 1-ft.² (0.1 m²) pan fire.

Fuel	Range (ft./m)
Gasoline	50/15
n-Heptane	50/15
Diesel fuel	37/11
JP5	37/11
Kerosene	37/11
Ethanol 95%	29.5/9
Isopropyl alcohol (IPA)	37/11
Methanol	29.5/9
Methane ⁽¹⁾	33/10
Liquefied petroleum gas (LPG) ⁽¹⁾	33/10
Polypropylene pellets	33/10
Office paper	16/5
Hydrogen ⁽¹⁾	37/11
Magnesium alloy	16/5
Gun powder (1.5 in ² [10 cm ²])	33/10
Fireworks (10 pieces per test)	5/1.6
Cooking oil	37/11
Mineral oil (20w50)	37/11
Wood	16/5
Ethylene glycol	12/3.7
Butyl acrylate	37/11
Vinyl acetate	37/11
Flammable adhesive (flash point < 140 °F [60 °C])	37/11
Solvents	37/11
Oil paint	37/11
Jet A1	37/11
Battery ⁽²⁾	39/12

(1) 30-in. (0.75 m) high, 10-in (0.25 m) wide plume fire

(2) Lithium ion battery. Height: 2.56 in. (65 mm). Diameter: 0.72 in. (18.4 mm).

Table 2: General specifications

Spectral response	Ultraviolet: 0.185 to 0.260 μm Infrared: 2.5 to 3.0 μm
Detection response time	Standard response: typically < 5 sec
Sensitivity ranges	2 sensitivity ranges

Table 2: General specifications (continued)

Field of view	Horizontal: 100° Vertical: 95 °
Coverage area	12,999 ft ² (3962 m ²)
Temperature range	Operating: -40 to +167 °F (-40 to +75 °C) Storage: -40 to +167 °F (-40 to +75 °C)
Humidity	Non-condensing relative humidity up to 100%

Table 3: Electrical specifications

Operating voltage	24 Vdc nominal (18-32 VDC)
Cable entries	2 x ¾-in. -14 NPT conduits or 2 x M25 x 1.5 mm ISO
Electrical input protection	According to EN 50130
Electromagnetic compatibility	EMI/RFI protected to EN61000-6-3 and EN 50130
Electrical interface	The detector includes 17 terminals and one wiring option.

Table 4: Typical power consumption (24 Vdc)

Mode	mA	Watts
Normal without heater	60	1.4
Normal without heater with alarm	90	2.2
Standard power mode heater with alarm	310	7.7

Table 5: Outputs

Relays	Alarm, fault, and auxiliary SPST volt-free contacts rated 2 A at 30 Vdc
Analog output	Analog port malfunction: 0 V (< 0.5 V) Normal: 2 V ± 0.3 V Alarm: 5 V ± 0.3 V
0-20 mA (stepped)	Fault: 0 ± 1 mA Built-in test (BIT) fault: 2 mA ± 0.3 mA Normal: 4 mA ± 0.3 mA Warning: 16 mA ± 0.3 mA Alarm: 20 mA ± 0.3 mA
HART® protocol	HART communication on the 0-20 mA analog current (FSK) used for maintenance, configuration changes, and asset management, available in mA source output wiring options
RS-485	RS-485 Modbus® compatible communication link that can be used in computer controlled installations

Table 6: Mechanical specifications

Enclosure options	Heavy duty copper free aluminum (less than 1%), polyurethane painted
Mounting	Electropolished stainless steel 316
Dimensions	Detector: 4 x 4.6 x 6.18 in. (100.6 x 117 x 155 mm)
Weight	Detector aluminum: 2.8 lb (1.3 kg) Tilt mount: 2.5 lb (1.1 kg)
Water and dust	IP66 and IP68 per EN60529, NEMA® 250 6P

Approvals

For approvals information, see [Spectrex 40/40 Series Certification Information](#).

For more information: [Spectrex.net](https://www.spectrex.net)

©2024 Emerson. All rights reserved.

Spectrex is a mark of one of the Emerson family of companies. All other marks are the property of their respective owners.

